



PRODUCT & TECHNICAL DATA

PRO ROCKDRILL OIL RANGE

LUBRICANT FOR PNEUMATIC ROCK DRILL EQUIPMENT

DESCRIPTION

Pro Rockdrill Oils are blended from high quality base oils and contains extreme pressure additives, suitable for use in all rock drills.

Pro Rockdrill Oils are available in VG 100, 150, 220 and 320.

APPLICATIONS

Pro Rockdrill Oils are mostly used in the Mining, and Industrial, sector that are subjected to severe operations, encountered in any other lubricant application (dust, dirt and moisture).

Factors, under which Pro Rockdrill Oils work, include heavy loading, high speeds, high temperatures, acidic water, dirt and other solid impurities, enclosed working environment and even hostile and abusive operation by the machine operator. Taking all these factors into consideration, Pro Rockdrill Oils will deliver extended protection.

FEATURES AND ADVANTAGES

- Outstanding protection against wear.
- Excellent resistance to corrosion.
- Reduction in pneumatic hammer wear.
- Excellent resistance to water wash out.

PRO ROCKDRILL OIL RANGE

PRODUCT AND TECHNICAL DATA

PHYSICAL CHARACTERISTICS

ISO VG	100	150	220	320
Viscosity @ 40 °C, mm ² /s	100	150	220	320
Flash Point, °C	230	240	240	250
Density @ 20 °C, g/ml	0.881	0.895	0.904	0.911

GENERAL ADVICE

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:
www.prooil.co.za

These characteristics are typical of current production.
Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA (PTY) LTD and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

For more information, contact: Pro Oil SA (PTY) LTD
Unit 3, Shalem Park
60 Lauda Road
Killarney Gardens
Cape Town
South Africa
7411

Technical Advice Line: (+27) 21 556 6109
Customer Service: (+27) 21 556 6109