



PRODUCT & TECHNICAL DATA

PRO PROCESS OIL RANGE

PREMIUM QUALITY, GROUP II (2), MANUFACTURING PROCESS OILS

DESCRIPTION

Pro Process Oil range are light viscosity virgin mineral oils. They contain no additives and therefore their applications are restricted to the use as a raw material in the manufacturing process.

APPLICATIONS

Pro Process Oils are suitable for use in the manufacturing of polishes, rubber based products, water proofing compounds wood preservatives, rope and twine dressings, etc. Also suitable for use in fertilizer, farm feeds and agricultural applications as long as the Act 36/1947 is complied with, in that no more than 80grams of oil per 1kg feed is added and therefore shall be registered as an animal feed if anti-oxidant, which is approved by the Register, is added thereto. Provided that if the Register is, in respect of particular product, satisfied that the addition of an anti-oxidant is undesirable, he/she may determine that such an addition need not be made.

FEATURES AND ADVANTAGES

- Group II base oils.
- Consistent in quality.
- Contains no additives.
- Used in manufacturing of polishes, rubber based products, farm feeds and more.
-

PRO PROCESS OIL RANGE

PRODUCT AND TECHNICAL DATA

PHYSICAL CHARACTERISTICS

Appearance	Bright, Clear	Bright, Clear	Bright, Clear	Bright, Clear
ISO VG	20	30	100	150
Viscosity @ 40 °cSt, ASTM D 445	20	30	100	150
Viscosity Index, ASTM 2270	98	98	98	98
Pour Point, °C, ASTM D 97	-15	-9	-6	-5
Flash Point, °C, COC, (Min)	200	200	200	200
Density @ 20 °C, ASTM 1298	0.84	0.85	0.87	0.89

GENERAL ADVICE

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:
www.prooil.co.za

These characteristics are typical of current production.
Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA (PTY) LTD and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

For more information, contact: Pro Oil SA (PTY) LTD
Unit 3, Shalem Park
60 Lauda Road
Killarney Gardens
Cape Town
South Africa
7411

Technical Advice Line: (+27) 21 556 6109
Customer Service: (+27) 21 556 6109