



PRODUCT & TECHNICAL DATA

PRO REVOLUSYN 25W50 CI-4/SL

MULTIGRADE DIESEL AND PETROL ENGINE OIL FOR HIGH MILEAGE VEHICLES

DESCRIPTION

Pro Revolusyn 25W50 CI-4 is a uniquely formulated multigrade engine oil, specially engineered to provide specific benefits to meet the most difficult and arduous operating conditions. It is particularly designed for high mileage, out of warranty engines. Pro Revolusyn 25W50 stays within viscosity rating with up to 6% fuel dilution. It is blended from high quality, solvent neutralized hydrocarbon, semi-synthetic (Group 2), virgin base oils and is supported with the latest technology in multifunctional additive packs.

APPLICATIONS

Pro Revolusyn is recommended for use in naturally aspirated and turbo diesel engines for both on and offroad highway, heavy and light duty vehicles, where oil pressure is required. It is also recommended for engines that experience fuel dilution. Due to its API petrol engine specification, it is also ideal for petrol engines with high mileage where oil consumption is higher than normal and where oil pressure is a problem.

PERFORMANCE LEVELS

- API CI-4 / SL
- CAT TO-2
- MIL-L-2104D / 46152C

FEATURES AND ADVANTAGES

- Reduced oil consumption.
- Maintains oil pressure.
- Optimum engine reliability and operational economy.
- Exceptional tolerance to fuel dilution.
- Excellent TBN retention, throughout the service of the oil.
- Reduced blow by, means improved compression.
- Viscosity of 25W50 offers good oil consumption for worn engines.

PRO REVOLUSYN 25W50 CI-4/SL

PRODUCT AND TECHNICAL DATA

PHYSICAL CHARACTERISTICS

SAE	25W50
Viscosity @ 40 °cSt	220
Viscosity @ 100 ° cSt	20.10
Viscosity Index	103
Pour Point, °C	-19
Flash Point, °C	>200
Density @ 20 °C, kg/l	0.886
Total Base Number, mg, KOH/g	11.16

GENERAL ADVICE

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:
www.prooil.co.za

These characteristics are typical of current production.
Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA (PTY) LTD and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

For more information, contact: Pro Oil SA (PTY) LTD
Unit 3, Shalem Park
60 Lauda Road
Killarney Gardens
Cape Town
South Africa
7411

Technical Advice Line: (+27) 21 556 6109
Customer Service: (+27) 21 556 6109