



PRODUCT & TECHNICAL DATA

PRO EXTREME GEAR GL-5 85W140

HEAVY DUTY HYPOID GEAR DIFFERENTIAL LUBRICANT

DESCRIPTION

Pro Extreme Gear GL-5 85W140 is a premium quality, multipurpose gear lubricant blended from Group II base oils and internationally approved additive packs. It meets the rigorous demands of commercial fleet manual transmissions, drive axles and final drives. These products are also suitable for similar components of farm and earth moving equipment and passenger cars where GL-5 API service classification is required.

APPLICATIONS

Pro Extreme Gear GL-5 85W140 is suitable for hypoid gear differentials operating under high speed and or low speed, high torque conditions. It is also suitable for heavy duty non-synchronized manual transmissions and transaxles requiring this type of lubricant, as well as automotive steering gears. Not to be used in such applications where the manufacturer advises against the use of an API GL-5 lubricant.

PERFORMANCE LEVELS

- API GL-5
- MIL-L-2105D
- ISO 9001/2008

FEATURES AND ADVANTAGES

- Reduced maintenance costs.
- Resistance to high temperature oxidation.
- Extended gear equipment life.
- Protection against wear & scoring under all conditions including high torque shock loading.

PRO EXTREME GEAR GL-5 85W140

PRODUCT AND TECHNICAL DATA

PHYSICAL CHARACTERISTICS

Viscosity @ 40 °cSt	355.04
Viscosity @ 100 ° cSt	24.583
Viscosity Index	92
Pour Point, °C	-13
Flash Point, °C (Max)	>200
Density @ 20 °C, kg/l	0.8994
Total Acid Number	0.70

PRODUCT AND TECHNICAL DATA

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:
www.prooil.co.za

These characteristics are typical of current production.
Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA (PTY) LTD and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

For more information, contact: Pro Oil SA (PTY) LTD
Unit 3, Shalem Park
60 Lauda Road
Killarney Gardens
Cape Town
South Africa
7411

Technical Advice Line: (+27) 21 556 6109
Customer Service: (+27) 21 556 6109