



PRODUCT & TECHNICAL DATA

PRO VELOSYN 5W30

FULL SYNTHETIC, HIGH PERFORMANCE, MULTIGRADE ENGINE OIL - C3 LOW SAPS

DESCRIPTION

Pro Velosyn 5W30 C3 Low Saps is a full synthetic, multigrade, engine oil. It is specifically formulated for Multi-Valve high speed engines equipped with turbocharged and direct injection fuel systems. Pro Velosyn 5W30 Low Saps additive technology (low content in sulphated ash phosphorus and sulphur) makes it the lubricant of choice for optimal operation of the latest engine generation equipped with anti-pollutant devices such as diesel particulate filters, (DPF) and exhaust catalyts.

APPLICATIONS

Pro Velosyn 5W30 as a synthetic based oil, with the latest in additive technology, is recommended for use in all types of modern vehicles with extended service intervals or high performance turbo-charged engines, especially those fitted with hydraulic tappets. Pro Velosyn 5W30 is particularly suitable for all petrol and diesel passenger cars and light commercial vehicles. The unique base provides exceptional oxidation stability and outstanding engine cleanliness, which is critical for optimum performance.

PERFORMANCE LEVELS

- API SN/CF
- ACEA C3
- Porsche A40 / C30
- Renault RN0710 / RN0700
- MB 229.51 / 229.52 / 229.31
- VW 504.00 / 507.00
- VW 502.00 / 505.01
- BMW LL-04 MB 226.5
- Ford 917A / M2C-917A
- Dexos 2

FEATURES AND ADVANTAGES

- Ensures longer life of emission control devices and better engine performance and fuel economy.
- Demonstrates excellent high-temperature/high shear (HT/HS) performance to maintain viscosity and to provide adequate engine Protection.
- Can be used in all Euro 4 and Euro 5 trucks and fleets.
- Maintains the efficiency of exhaust after treatment systems, ensuring continued compliance with emission legislation.

PRO VELOSYN 5W30

PRODUCT AND TECHNICAL DATA

PHYSICAL CHARACTERISTICS

SAE	5W30
Viscosity @ 40 °cSt	83
Viscosity @ 100 ° cSt	13.64
Viscosity Index	168
Pour Point, °C	-40
Flash Point, °C	220
Density @ 20 °C, kg/l	0.852
Total Base Number	8.11

GENERAL ADVICE

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:
www.prooil.co.za

These characteristics are typical of current production.
Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA (PTY) LTD and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

For more information, contact: Pro Oil SA (PTY) LTD
Unit 3, Shalem Park
60 Lauda Road
Killarney Gardens
Cape Town
South Africa
7411

Technical Advice Line: (+27) 21 556 6109
Customer Service: (+27) 21 556 6109