



PRODUCT & TECHNICAL DATA

PRO UNI-CUT 430

PREMIUM QUALITY, GROUP II, UNIVERSAL NEAT CUTTING FLUID

DESCRIPTION

Pro Uni-Cut 430 is a universal, multi-functional, group II (2) lubricant with chlorinated additives to provide exacting results. Pro Uni-Cut 430 is a highly specialized oil, engineered to be used firstly as a cutting fluid, but in some cases also to be used as a hydraulic / circulating medium where needed and can also be used as a slideway lubricants were appropriate.

APPLICATIONS

Pro Uni-Cut 430 is a multi-functional, group II (2) (in base stock) product and can be successfully applied to gear generation by the shaving or sharpening techniques. It can also be used for selected heavy duty cutting operations on steel up to 65 tons/sq. inch tensile. The universal nature of the product makes it equally suitable to slideway applications.

FEATURES AND ADVANTAGES

- Group II cutting lubricant
- Reduces number of grades of oil held in stock, with less risk of cross contamination and saving storage spaces as well as capital outlay
- Ensuring excellent cutting performance, tool life and surface finish
- System leakage between hydraulic or slideway systems into the cutting oil does not reduce cutting performance, thus ensuring improved tool life and surface finish.
- Contains high tech performance enhancing additives.



PRODUCT AND TECHNICAL DATA

PHYSICAL CHARACTERISTICS

Colour	Clear
Additives	Chlorine, Anti-Rust, Anti-Wear, Anti-Oxidant
Viscosity @ 40 °cSt	35
Viscosity Index	115
Base	Group II (2)
Flash Point, °C	233
Density @ 20 °C, kg/l	0.0877

GENERAL ADVISE

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:

www.prooil.co.za

These characteristics are typical of current production.

Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

Health & Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

For more information contact: Pro Oil SA
Unit 1, Dale Park
Killarney Gardens
Cape Town
South Africa
7411

Technical Advice Line: (+27) 21 556 6109
Customer Service: (+27) 21 556 6109

30/01/2013

