



PRODUCT & TECHNICAL DATA

PRO MULTIFARM 15W40 CF-4/SF

SUPER TRACTOR OIL UNIVERSAL (STOU)

DESCRIPTION

Pro Multifarm 15W40 is a multigrade super tractor oil universal (STOU), which is designed primarily for use in both normally aspirated and turbo charged diesel engines, most transmissions and hydraulic systems found on modern agriculture implements. It is designed to maximise the protection of agricultural equipment, thereby reducing maintenance costs, downtime and extending the equipment's running life. Pro Multifarm 15W40 is formulated from HVI Base Oils and high performance internationally formulated additives.

APPLICATIONS

Pro Multifarm 15W40 can be used in transmissions, hydraulic systems, final drives, power steering systems and fluid immersed disc brakes in agricultural and industrial tractors and similar equipment.

PERFORMANCE LEVELS

- Massey Ferguson M-1127, M-1135, M-1139, M- 1144
- John Deere JDM J27, J20A & J20 C
- Ford ESN-M2C-159C & M2C134D
- Case IHMS 1207
- Mercedes Benz 227.1
- API CF-4/SF, API GL4, API GL5 (low speed high torque)
- Allison C4 & CAT TO-2
- MIL-L-2104D – CLMC D4
- Ford New Holland

FEATURES AND ADVANTAGES

- One oil for the farm.
- Excellent anti-squawk properties.
- Excellent rust and corrosion protection.
- High oxidation stability protects against the formation of gums and varnish.
- Outstanding control of low temperature sludge & deposits.

PRO MULTIFARM 15W40 CF-4/SF

PRODUCT AND TECHNICAL DATA

PHYSICAL CHARACTERISTICS

SAE / API	15W40 / GL-4 & GL-5 (Low Speed, High Torque)
Viscosity @ 40 °cSt	115.30
Viscosity @ 100 ° cSt	14.02
Viscosity Index	127
Pour Point, °C	-28
Flash Point, °C	>200
Density @ 20 °C, kg/l	0.8664
Total Base Number, mg, KOH/g	9.50

GENERAL ADVICE

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:
www.prooil.co.za

These characteristics are typical of current production.
Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA (PTY) LTD and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

For more information, contact: Pro Oil SA (PTY) LTD
Unit 3, Shalem Park
60 Lauda Road
Killarney Gardens
Cape Town
South Africa
7411

Technical Advice Line: (+27) 21 556 6109
Customer Service: (+27) 21 556 6109