



PRODUCT & TECHNICAL DATA

PRO UNITRAC TRANS 10W30

UNIVERSAL TRACTOR TRANSMISSION OIL (UTTO)

DESCRIPTION

Pro Unitrac Trans 10W30 is a Universal Tractor Transmission Oil, for use as a power transmission lubricant, which is specifically formulated to provide excellent anti-wear properties. The additive pack has been designed to prevent squawk and chatter.

APPLICATIONS

Pro Unitrac Trans 10W30 is designed for use in the hydraulic/transmission units where tractors are fitted with paper immersed brake systems and requiring a low viscosity lubricant. The additive pack also provides excellent oxidation stability and frictional control, which makes it suitable for use in power shift transmission systems and applications requiring Allison C4 type fluids.

PERFORMANCE LEVELS

- Case International JIC 145/MS 1210 JIS 185/MS 1204 MS 1205 MS 1206
- Ford M2C194/AB/C/D M2C41B M2C53A
- John Deere J20C & J20D
- Massey Ferguson M1135, M1141, M1110, M1127, M1129A
- API GL-4 low speed high torque CRC 120
- Denison HF-1, HF-2
- Sperry Vickers 1-286S M2950S
- Caterpillar TO-2
- Ford New Holland
- Allison C-4

FEATURES AND ADVANTAGES

- Enhanced wet brake performance reducing the possibility of premature brake failure.
- Specially formulated to give excellent power take off under demanding situations.
- Excellent low temperature fluid and anti-foam characteristics.
- Improved hydraulic performance minimizing both rust and wear.

PRO UNITRAC TRANS 10W30

PRODUCT AND TECHNICAL DATA

PHYSICAL CHARACTERISTICS

SAE	80W
Viscosity @ 40 °cSt	59.50
Viscosity @ 100 ° cSt	10.34
Viscosity Index	138
Pour Point, °C	-35
Density @ 20 °C, kg/l	0.872

PRODUCT AND TECHNICAL DATA

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:
www.prooil.co.za

These characteristics are typical of current production.
Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA (PTY) LTD and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

For more information, contact: Pro Oil SA (PTY) LTD
Unit 3, Shalem Park
60 Lauda Road
Killarney Gardens
Cape Town
South Africa
7411

Technical Advice Line: (+27) 21 556 6109
Customer Service: (+27) 21 556 6109