



## PRODUCT & TECHNICAL DATA

# PRO UBER ALL EP 3

## GENERAL PURPOSE LITHIUM GREASE

### DESCRIPTION

Pro Uber All EP 3 is a multi-purpose grease incorporating an extreme pressure additive package, which possesses the additional advantage of improving corrosion protection. Pro Uber All EP 3 is based on high quality base oils blended with a lithium thickening agent and possesses excellent mechanical stability, as well as good load carrying, anti-corrosion and water-resisting properties. This grease is suitable for operations between -30 to 130 °C.

### APPLICATIONS

Pro UberAll EP 3 is designed for use in highly loaded plain and roller bearings as well as for shock loading conditions in the mining industry and steel mills. It is suitable for use in the full range of bearing speeds encountered in electric motors, machine and wood working tools, production equipment, textile and paper making industry, generators and all types of vehicles. The smooth consistency makes these greases ideal for use in centralized lubrication systems and they can be used on ferrous and non-ferrous metals.

### FEATURES AND ADVANTAGES

- Protects against rust and corrosion.
- Resistance to water washing.
- Good resistance to oxidation.

# PRO UBER ALL EP 3

## PRODUCT AND TECHNICAL DATA

### PHYSICAL CHARACTERISTICS

Thickening Agent	Lithium
NLGI	3
Work Penetration @ 25 °C	220 - 250
Appearance, Visual	Light Brown, Brown
Drop Point, °C	>185
Timken OK Load, kg	>27
Base Oil Viscosity @ 40 °C	230
Recommended Temperature Range	-30° to 130°C

## PRODUCT AND TECHNICAL DATA

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:  
[www.prooil.co.za](http://www.prooil.co.za)

These characteristics are typical of current production.  
Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

### Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA (PTY) LTD and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

For more information, contact: Pro Oil SA (PTY) LTD  
Unit 3, Shalem Park  
60 Lauda Road  
Killarney Gardens  
Cape Town  
South Africa  
7411

Technical Advice Line: (+27) 21 556 6109  
Customer Service: (+27) 21 556 6109