



PRODUCT & TECHNICAL DATA

PRO ARCTICAIR M 68

NAPHTHENIC REFRIGERATION COMPRESSOR OIL VG 68

DESCRIPTION

Pro Arcticair M 68 is a high quality naphthenic mineral oil. It is used in rotary and reciprocating refrigeration compressors. It has excellent fluidity at low temperatures and improves heat transfer.

Pro Arcticair M 68 has excellent lubricity characteristics and due to improved heat distribution, will save energy.

APPLICATIONS

Pro Arcticair M 68 is suitable for both rotary and reciprocating refrigeration compressors. It can be used with R12, R22 and ammonia refrigerants. It is miscible with most refrigerants, except sulphur dioxide and HFC - 134a.

FEATURES AND ADVANTAGES

- High oxidation and corrosion resistance.
- Excellent lubricity – decrease energy consumption.
- Longer drain intervals.
- Will not leave carbon deposits.
- Quick air separation.
- Very good demulsibility.
- Better heat distribution.

PRO ARCTICAIR M 68

PRODUCT AND TECHNICAL DATA

PHYSICAL CHARACTERISTICS

Viscosity Grade	68
Density @ 20°C	0.910
Viscosity @ 40°C	68
Pour Point, °C	<-45
Flash Point, °C	>180

GENERAL ADVICE

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:
www.prooil.co.za

These characteristics are typical of current production.
Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA (PTY) LTD and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

For more information, contact: Pro Oil SA (PTY) LTD
Unit 3, Shalem Park
60 Lauda Road
Killarney Gardens
Cape Town
South Africa
7411

Technical Advice Line: (+27) 21 556 6109
Customer Service: (+27) 21 556 6109