



PRODUCT & TECHNICAL DATA

PRO ATF DX II

AUTOMATIC TRANSMISSION FLUID (ATF)

DESCRIPTION

Pro ATF DX II is a high quality automatic transmission fluid (ATF), formulated from High Viscosity Index virgin base oils combined with viscosity index improvers, anti-oxidants, anti-wear agents, detergents, dispersants and special additives to provide the controlled frictional characteristics required to meet the requirements of automatic transmissions.

APPLICATIONS

Pro ATF DX II is used in car and light truck automatic transmissions as well as on and off-highway heavy-duty automatic transmissions and power steering systems.

PERFORMANCE LEVELS

- CATERPILLAR T0-2
- VOITH
- ZF TE –ML 09, ZF TE –ML 11, ZF TE –ML 14
- DENISON
- SUNSTRAND
- ISO 9001/2008

FEATURES AND ADVANTAGES

- Excellent lubrication at all operating temperatures
- Protection against wear & corrosion
- Correct frictional properties for each type of automatic transmission
- Better performance as a result of foam resistance
- Protection against deposit formation

PRO ATF DX II

PRODUCT AND TECHNICAL DATA

PHYSICAL CHARACTERISTICS

Appearance	Red
Viscosity @ 40 °cSt	37.39
Viscosity @ 100 ° cSt	7.23
Viscosity Index	161
Pour Point, °C	-45
Flash Point, °C (PMCC)	153-155
Density @ 20 °C, kg/l	0.854

GENERAL ADVICE

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:
www.prooil.co.za

These characteristics are typical of current production.
Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA (PTY) LTD and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

For more information, contact: Pro Oil SA (PTY) LTD
Unit 3, Shalem Park
60 Lauda Road
Killarney Gardens
Cape Town
South Africa
7411

Technical Advice Line: (+27) 21 556 6109
Customer Service: (+27) 21 556 6109