



PRODUCT & TECHNICAL DATA

PRO MULTIGEAR GL-4 80W90

GEARBOX LUBRICANT

DESCRIPTION

Pro Multigear GL-4 80W90 is a premium automotive gear lubricant containing extreme pressure additives and blended with virgin base oils. It is especially recommended for synchromesh transmissions where they provide full protection to bronze components, ensuring reliable operation and smooth changes.

APPLICATIONS

Pro Multigear GL-4 80W90 is suitable for transmission gearboxes and other applications, which require a relatively low level of extreme pressure additives.

PERFORMANCE LEVELS

- API GL-4
- MIL-L-2105
- ISO 9001/2008

FEATURES AND ADVANTAGES

- High quality oil manual transmission oil with synchromesh compatibility.
- Compatible with most other mineral gear oils.
- Contains an extreme pressure additive to cope with high loading.
- Excellent protection against wear and corrosion.
- Offers good oxidation and thermal stability.

PRO MULTIGEAR GL-4 80W90

PRODUCT AND TECHNICAL DATA

PHYSICAL CHARACTERISTICS

Viscosity @ 40 °cSt	136.16
Viscosity @ 100 ° cSt	14.41
Viscosity Index	104
Pour Point, °C	-30
Flash Point, °C (Max)	>200
Density @ 20 °C, kg/l	0.8724
Total Acid Number	0.70

PRODUCT AND TECHNICAL DATA

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:
www.prooil.co.za

These characteristics are typical of current production.
Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA (PTY) LTD and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

For more information, contact: Pro Oil SA (PTY) LTD
Unit 3, Shalem Park
60 Lauda Road
Killarney Gardens
Cape Town
South Africa
7411

Technical Advice Line: (+27) 21 556 6109
Customer Service: (+27) 21 556 6109