



PRODUCT & TECHNICAL DATA

PRO EXTREME GEAR GL-5 EP 90

MANUAL GEAR, TRANSAXLES, HUB AND SPUR LUBRICANT

DESCRIPTION

Pro Extreme Gear GL-5 EP 90 is a high performance, multipurpose automotive gear oil. It is blended from, Group 2, base oils, which have been fortified with anti-wear, anti-oxidant, anti-foam, anti-corrosion and extreme pressure additives.

APPLICATIONS

Pro Extreme Gear GL-5 EP 90 is suitable for manual transmissions, transaxles, planetary hub & other spur gear axles which specifically require EP gear oils meeting API GL-5.

PERFORMANCE LEVELS

- MIL-2105 -D
- MB 235.1 / MB 235.5
- MAN 342N

FEATURES AND ADVANTAGES

- High performance, EP additive system controls transmission gear tooth wear, excellent load carrying capacity to protect gear equipment against surface stress under heavily loaded conditions.
- GL-5 gear oils have been fortified with anti-wear, anti-oxidant, anti-foam, anti-corrosion and extreme pressure additives.

PRO EXTREME GEAR GL-5 EP 90

PRODUCT AND TECHNICAL DATA

PHYSICAL CHARACTERISTICS

Viscosity @ 40 °cSt	158
Viscosity @ 100 ° cSt	15.36
Viscosity Index	106.70
Pour Point, °C	-17
Flash Point, °C (Max)	220
Density @ 20 °C, kg/l	0.8896

PRODUCT AND TECHNICAL DATA

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:
www.prooil.co.za

These characteristics are typical of current production.
Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA (PTY) LTD and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

For more information, contact: Pro Oil SA (PTY) LTD
Unit 3, Shalem Park
60 Lauda Road
Killarney Gardens
Cape Town
South Africa
7411

Technical Advice Line: (+27) 21 556 6109
Customer Service: (+27) 21 556 6109