



## PRODUCT & TECHNICAL DATA

# PRO TWO STROKE OIL

## TWO STROKE ENGINE OIL

### DESCRIPTION

Pro Two Stroke Oil is specially formulated using virgin base oil and selective additive pack in order to meet the API TC specification.

### APPLICATIONS

Pro Two Stroke Oil is recommended for the lubrication of all two-stroke, air-cooled petrol engines, i.e. motorcycles, mopeds, lawn mowers, chain saws etc. Manufacturers' recommendations should be followed to ensure correct oil/fuel mixture, but as a general guide a mixture of one-part oil to twenty parts petrol would be suitable for the above equipment.

PLEASE NOTE: This oil is not to be used in outboard engines. Please refer to Pro Super Outboard Oil.

### PERFORMANCE LEVELS

- API-TC
- JASO FB

### FEATURES AND ADVANTAGES

- Low ash oil exhibits excellent anti-wear properties.
- Freedom from ring sticking and exhaust port blocking.
- Freedom from plug fouling and piston crown deposits.

# PRO TWO STROKE OIL

## PRODUCT AND TECHNICAL DATA

### PHYSICAL CHARACTERISTICS

Colour	Blue
Viscosity @ 40 °cSt	76.10
Viscosity @ 100 ° cSt	15.21
Pour Point, °C	-21
Total Base Number, mg, KOH/g	2.60
Sulphated Ash %	0.08

### GENERAL ADVICE

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:  
[www.prooil.co.za](http://www.prooil.co.za)

These characteristics are typical of current production.  
Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

#### Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA (PTY) LTD and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

For more information, contact: Pro Oil SA (PTY) LTD  
Unit 3, Shalem Park  
60 Lauda Road  
Killarney Gardens  
Cape Town  
South Africa  
7411

Technical Advice Line: (+27) 21 556 6109  
Customer Service: (+27) 21 556 6109