



REGISTERED FIRM

Contact Information:
e-Mail: polichem@mweb.co.za
Telephone: (011) 918 2955
Facsimile: (011) 918 2956
REG NO. 2002/015336/07
VAT NO. 4220199527

FLEET WASH

Technical Data Sheet

Section I - Product Description

Fleet Wash is a non-caustic detergent.

Section II - Recommended Dilution Ratios

HEAVY DUTY: 50% : 500ml/L
MEDIUM DUTY: 10% : 100ml/L
LIGHT DUTY: 1% : 10ml/L

Fleet Wash is suitable for cleaning Trucks, vehicles and for removal of grease and oil from workshop floors/engines etc.

Fleet Wash is highly concentrated and can be diluted to your requirements.

Section III - Features and Benefits

Fleet Wash has a blend of solvents to dissolve stubborn oil and grease from most surfaces.

Fleet Wash has an optimum level of wetting agents to enable it to penetrate porous surfaces and be effective, yet still rinse off easily.

Fleet Wash is non-caustic and therefore completely safe for use on most surfaces.

Fleet Wash contains sequestering agents which enables it to be used in hard or soft water areas effectively.

Fleet Wash is volatile and therefore should be stoppered on storage.

Fleet Wash has anti corrosion agents built in to reduce corrosion.

Section IV - Packaging

Fleet Wash is packed in 200L plastic drums. Store at room temperature in stoppered containers.

Section V - Safety Precautions

SKIN:

Prolonged contact with skin should be avoided.

EYE CONTACT:

For accidental eye contact, bathe well with copious water and seek medical advice.

Section VI - Recommendations

Fleet Wash contains detergents and solvents and therefore all surfaces should be thoroughly rinsed with water after cleaning.