



PRODUCT & TECHNICAL DATA

PRO VELOCITY 5W40

FULL SYNTHETIC MULTIGRADE ENGINE OIL

DESCRIPTION

Pro Velocity is a Full Synthetic SAE 5W40 blended with Group III, synthetic type base oils using an advanced Heat Seek Technology (HST) additive package, which is unique to the Pro Oil SA brand, developed with a non-dispersant V.I Improver. It provides high temperature stability and can withstand severe service conditions. It has a proven ability to reduce both oil and fuel consumption. It also allows for longer oil drain intervals and eliminates cylinder wear. Pro Velocity is a proven 5W40 Full Synthetic engine oil. This oil is also suitable for diesel engines calling for a CF specification.

APPLICATIONS

Pro Velocity 5W40 as a synthetic based oil, with the latest in additive technology, is recommended for use in all types of modern vehicles with extended service intervals or high performance turbo-charged engines, especially those fitted with hydraulic tappets. Pro Velocity 5W40 is particularly suitable for all petrol and diesel passenger cars and light commercial vehicles. The unique base provides exceptional oxidation stability and outstanding engine cleanliness, which is critical for optimum performance.

PERFORMANCE LEVELS

- API CF / SM / SN
- PORCHE A40
- RENAULT RN 710/700
- ACEA A3/B4-08
- MB 229.3 / 229.5
- OPEL GM-LL-B-025
- BMW LL-01
- VW 502.00 / 505.00

FEATURES AND ADVANTAGES

- Improved fuel economy and power output.
- Reduced wear and increased engine life.
- Proven ability to reduce fuel and oil consumption.
- Excellent levels of engine cleanliness.
- Exceptional anti-wear and detergency level.
- Longer oil drain intervals.
- Can withstand severe service conditions.
- Excellent low temperature properties.

PRO VELOCITY 5W40

PRODUCT AND TECHNICAL DATA

PHYSICAL CHARACTERISTICS

SAE	5W40
Viscosity @ 40 °cSt	96.15
Viscosity @ 100 ° cSt	15.23
Viscosity Index	167.5
Pour Point, °C	-42
Flash Point, °C	>226
Density @ 20 °C, kg/l	0.852

GENERAL ADVICE

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:
www.prooil.co.za

These characteristics are typical of current production.
Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA (PTY) LTD and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

For more information, contact: Pro Oil SA (PTY) LTD
Unit 3, Shalem Park
60 Lauda Road
Killarney Gardens
Cape Town
South Africa
7411

Technical Advice Line: (+27) 21 556 6109
Customer Service: (+27) 21 556 6109