



PRODUCT & TECHNICAL DATA

PRO WIRE ROPE DRESSING

WIRE ROPE DRESSING (70-100 with solvent)

DESCRIPTION

Pro Wire Rope Dressing is a black, high viscous and adhesive bitumen-based lubricant with long-lasting protection over a wide range of operating conditions and equipment requirements.

APPLICATIONS

Pro Wire Rope Dressing is formulated to lubricate wire ropes, open gears and pinions under the exposure to the elements. It contains a volatile non-flammable solvent for easier application.

FEATURES AND ADVANTAGES

- Rust and corrosion protection.
- Resistance to fling-off during high winding speeds.
- Wear protection.
- Water repellent and insolubility.
- Good storage and service stability.

PRO WIRE ROPE DRESSING

PRODUCT AND TECHNICAL DATA

PHYSICAL CHARACTERISTICS

Colour	Black
Base Oil Viscosity @ 110 °C, mm ² /s	70-100 (with solvent)
Base Oil Viscosity @ 110 °C, mm ² /s	50-180 (without solvent)
Pour Point, °C	0 to 5
Flash Point, °C, COC	>200
Density @ 20 °C, g/cm ³	1.03

PRODUCT AND TECHNICAL DATA

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:
www.prooil.co.za

These characteristics are typical of current production.
Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA (PTY) LTD and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

For more information, contact: Pro Oil SA (PTY) LTD
Unit 3, Shalem Park
60 Lauda Road
Killarney Gardens
Cape Town
South Africa
7411

Technical Advice Line: (+27) 21 556 6109
Customer Service: (+27) 21 556 6109