



## PRODUCT & TECHNICAL DATA

# PRO FG SEAMER OIL 150

**FOOD GRADE OIL FOR CAN SEAMING MACHINES IN THE FOOD INDUSTRY**

### DESCRIPTION

Pro FG Seamer Oil 150 is a food grade oil that is specifically manufactured and designed for can seaming machines. The unique formulating of this lubricant is a blend of hydrocarbon-based oils with synthetic ester components as well as synergistic additive combinations.

### APPLICATIONS

Pro FG Seamer Oil 150 is mainly used in the food industry. It is used on can seaming machines, where the canned food passes on a line and the lid of the can gets sealed onto the body of the can. This product facilitates the machine operation to run smoothly. Pro FG Seamer Oil 150 is formulated with ingredients meeting the FDA regulation 21 CFR 178.3570 for accidental food contact and NSF HX-1 registered raw materials that does not exceed the maximum concentrations.

### FEATURES AND ADVANTAGES

- NSF HX-1 registered raw materials.
- Food Grade Oil for accidental food contact.
- Excellent extreme pressure and anti-wear properties.
- Synthetic Ester components.
- Excellent corrosion protection properties.

# PRO FG SEAMER OIL 150

## PRODUCT AND TECHNICAL DATA

### PHYSICAL CHARACTERISTICS

Appearance	Clear Fluid
Viscosity @ 40 °cSt	150
Pour Point, °C	<-12
Flash Point, °C	>220
Density @ 20 °C, g/ml	0.857

### GENERAL ADVICE

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:  
[www.prooil.co.za](http://www.prooil.co.za)

These characteristics are typical of current production.  
Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

#### Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA (PTY) LTD and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

For more information, contact: Pro Oil SA (PTY) LTD  
Unit 3, Shalem Park  
60 Lauda Road  
Killarney Gardens  
Cape Town  
South Africa  
7411

Technical Advice Line: (+27) 21 556 6109  
Customer Service: (+27) 21 556 6109