



## PRODUCT & TECHNICAL DATA

# PRO ATF DX III

## SYNTHETIC AUTOMATIC TRANSMISSION FLUID (ATF)

### DESCRIPTION

Pro Automatic DX III is a premium quality automatic transmission fluid (ATF) formulated using synthetic type base oils including multifunctional additives with V.I. (Viscosity Improvers), anti-wear agents, detergents and dispersants plus red dye. It is suitable to give universal performance for extended periods of operation. It also provides the controlled frictional characteristics required to meet Allison C-4 requirements.

### APPLICATIONS

Pro Automatic DX III is recommended for use in automatic transmission and can be used in off-highway transmissions, power steering and other hydraulic applications.

### PERFORMANCE LEVELS

- DEXTRON (REGISTERED) IIID GENERAL MOTORS
- MERCON (REGISTERED) FORD MOTORS
- MERCEDES BENZ SHEET 236.81
- CATERPILLAR TO-2
- HAGGLUNDS DENISON HF-O
- ZF TE-ML 09, ZF TE-ML 11, ZF TE-ML 14
- SPERRY VICKERS HYDRAULIC PUMP SYSTEM

### FEATURES AND ADVANTAGES

- Excellent lubrication at all operating temperatures, even at below -40 °C.
- Protection against wear and corrosion.
- Correct frictional properties for each type of automatic transmission.
- Better performance as a result of foam resistance.
- Protection against deposit formation.

# PRO ATF DX III

## PRODUCT AND TECHNICAL DATA

### PHYSICAL CHARACTERISTICS

|                        |        |
|------------------------|--------|
| Appearance             | Red    |
| Viscosity @ 40 °cSt    | 39.15  |
| Viscosity @ 100 ° cSt  | 8.083  |
| Viscosity Index        | 186    |
| Pour Point, °C         | -54    |
| Flash Point, °C (PMCC) | 200    |
| Density @ 20 °C, kg/l  | 0.8480 |

### GENERAL ADVICE

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:  
[www.prooil.co.za](http://www.prooil.co.za)

These characteristics are typical of current production.  
Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

#### Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA (PTY) LTD and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

For more information, contact: Pro Oil SA (PTY) LTD  
Unit 3, Shalem Park  
60 Lauda Road  
Killarney Gardens  
Cape Town  
South Africa  
7411

Technical Advice Line: (+27) 21 556 6109  
Customer Service: (+27) 21 556 6109